








■ Contactless Angular Sensor



View from "B"




Ref.	Description	Operating Temperature °C
1	Cable HT 105°C	-40 / +105


		ELEN		industrial vehicles sensors		www.elensrl.com		Elen Srl - Garbagnate Milanese (MI)	
Rev.		Date		Sign.		Review Description		Part Number:	
1		16/05/2024		G.M.		Updated Cable Operating Temp. Data		Description:	
								Contactless Angular Sens. 5V+359°	
								Designed	
								15/05/2024	
								Giulia M.	
								Scale :	
								1 : 1 (A3 format)	
								Checked	
								15/05/2024	
								Approved	
								15/05/2024	
								Units	
								mm	
								Page 1 / 2	

■ Output Signals


Signal (V) @Vin = 5V



■ Functional Scheme



■ Typical Application



■ Technical Specifications

	Specific	Value	Standard Reference
Electrical	Power supply (Vcc)	Min 4.5V - Max 5.5V	ELEN PDV Rev. 3 - 5.1
	EMC Compatibility	BCI - Class "A" - 100mA ; 1~400 MHz	ISO 11452-4
	EMC Compatibility - Magn.Field Imm.	15Hz ÷ 150 kHz	ISO 11452-8 : 2007
	Reverse Polarity Protection	-5.5V For 1h	ELEN PDV Rev. 3 - 5.3
	Overload Protection	1,2mA For 1h	ELEN PDV Rev. 3 - 5.6
	Overvoltage Protection	6.5V For 1h	ELEN PDV Rev. 3 - 5.7
	Output Short Circuit Protection	To Ground For 5' To VDC For 5'	ELEN PDV Rev. 3 - 5.4
	Supply Current (No Load)	15 mA Max	ELEN PDV Rev.3 - 5.2
	Signal Output	[0.5V ÷ 4.5V]±0.2V	-
	Output Current	1 mA Max	ELEN PDV Rev. 3 - 5.5
	Dielectric Rigidity	750V@50Hz For 60s	ELEN PDV Rev. 3 - 5.11
	ESD Protection	±8kV Contact , ±15 kV Air	EN 61000-4-2
	Insulation Resitance	1000 MOhm@500V	ELEN PDV Rev. 3 - 5.10
	Temperature Operating Voltage	5.5V@105°C For 1h	ELEN PDV Rev. 3 - 5.8
	Resolution	12 bit	-
	Linearity	< ±1%	-
Environmental	Operating Temperature (for Electronic Components)	-40°C ÷ +105°C	IEC 60068-2-1 ; IEC 60068-2-2 ; IEC 60068-2-30 ;IEC60068-2-14
	Storage Temperature (for the Assembly)	-40°C ÷ +105°C	IEC 60068-2-1 ; IEC 60068-2-2 ; IEC 60068-2-30 ;IEC60068-2-14
	Degree Of Protection	IP 67	IEC 60529
	Vibrations Resistance - Sine	(5÷12.87) Hz@dis±15mm ,(12,87÷200) Hz@dis<±15mm@5g, 1 Octave/min , 20 Sweep Cycles	IEC 60068-2-6 ISO15998
	Vibrations Resistance - Random	f=10Hz@PSD=1.44 g2/Hz ; f=100Hz@PSD=3.85 g2/Hz ; f=1000Hz@PSD=3.85 g2/Hz ; f=2000Hz@PSD=0.96 g2/Hz ; 3 Axis - 24h For Axis	IEC 60068-2-64 ENS0310 Rev.J
Mech.	Body Material	Aluminium With Antioxidant Treatment	-
	Ext.Shaft Material	Stainless Steel	-