







■ Contactless Angular Sensor



$$A(2:1)$$


Ref.	Description	Operating Temperature °C
1	Cable HT 105°C	-25 / +105
2	6-Way Tyco Superseal Connector	-30 / +125


 ELEN industrial vehicles sensors				www.elensrl.com		Elen Srl - Garbagnate Milanese (MI)	
				Part Number:		AA020515-30	
				Description:		Contactless Angular Sensor +90° 12V	
Rev.	Date	Sign.	Review Description	Designed	02/12/2022	Giulia M.	Scale : 1 : 1 (A3 format)
1	06/12/22	G.M.	Rewieved Connector Description	Checked	02/12/2022		Dimensions without tolerance indication: ISO 2768 - m
				Approved	02/12/2022		 Units mm
				Page 1 / 2			

■ Output Signal


Signal 1 (V) @Vin = 10÷30V




Signal 2 (V) @Vin = 10÷30V



■ Functional Scheme



■ Typical Application



■ Technical Specifications

	Specific	Value	Standard Reference
Electrical	Supply Voltage (Vcc)	Min 10V - Max 30V	ELEN PDV Rev. 3 - 5.1
	Supply Current (No Load)	15mA Max (For Channel)	ELEN PDV Rev. 3 - 5.2
	Linear Output 1	0V ÷ 5V (2.5V @+45°)	-
	Linear Output 2	5V ÷ 0V (2.5V @+45°)	-
	Output Current	Max 20 mA (For Channel)	ELEN PDV Rev. 3 - 5.5
	EMC Compatibility	BCI - Class "A" - 100mA ; 1~400 MHz	ISO 11452-4
	Electrostatic Discharge Protection	±8kV Contact ; ±15kV Air Discharge	EN 61000-4-2
	Reverse Polarity Protection	-30V For 1h (-36V)	ELEN PDV Rev. 3 - 5.3
	Overload Protection	24 mA For 1h (50 mA)	ELEN PDV Rev. 3 - 5.6
	Overvoltage Protection	36V For 1h	ELEN PDV Rev. 3 - 5.7
	Resolution	0,1°	-
	Temperature Operating Voltage	30V @ 105°C For 1h	ELEN PDV Rev. 3 - 5.8
	Linearity Error	±1%	-
	Dielectric Rigidity	750V @ 50Hz For 60s	ELEN PDV Rev. 3 - 5.11
	Insulation Resistance	1000 MΩ @ 500V	ELEN PDV Rev. 3 - 5.10
Environmental	Shortcircuit Protection	To GND For 5' ; To Supply For 5'	ELEN PDV Rev. 3 - 5.4
	Operating Temperature (for Electronic Components)	-40°C ÷ +105°C	EN 60068-2-1;EN 60068-2-2; EN 60068-2-30;EN 60068-2-14
	Storage Temperature (for the Assembly)	-25° ÷ +105°C	EN 60068-2-1;EN 60068-2-2; EN 60068-2-30;EN 60068-2-14
	Degree of Protection	IP 67	IEC 60529
	Vibrations Resistance - Sine	(5÷12.87)Hz@dis±15mm, (12.87÷200)Hz@dis<±15mm@5g, 1 Octave/min, 20 Sweep Cycles	EN 60068-2-6; ISO 15998
Mech.	Vibrations Resistance - Random	f=10Hz@PSD=1.44 g2/Hz ; f=100Hz@PSD=3.85 g2/Hz ; f=1000Hz@PSD=3.85 g2/Hz ; f=2000Hz@PSD=0.96 g2/Hz ; 3 Axis - 24h For Axis	EN 60068-2-64 ENS 0310 Rev.J
	Body Material	Aluminium With Antioxidant Treatment	-
	Shaft Material	Stainless Steel	-