








■ Contactless Angular Sensor



Programming Alignment

X (3 : 1)



Ref.	Description	Operating Temperature °C
1	Cable HT 105°C	-25 / +105



www.elensrl.com Elen Srl - Garbagnate Milanese (MI)


Part Number: AA020515-31

Description: Contactless Angular Sens. 10-30V 0÷90°


Rev.	Date	Sign.	Review Description	Designed	20/01/2023	Matteo M.	Scale :	1 : 1 (A3 format)
1	09/09/2024	G.M.	Changed Shaft	Checked	-	-	Dimensions without tolerance indication: ISO 2768 - m	
				Approved	-	-	Units mm	Page 1 / 2

■ Output Signals


Signal (V) @Vin =
10V ÷ 30V



■ Functional Scheme



■ Typical Application



■ Technical Specifications

	Specific	Value	Standard Reference
Electrical	Power supply (Vcc)	Min 10V ÷ Max 30V	ELEN PDV Rev. 3 - 5.1
	EMC Compatibility	BCI - Class "A" - 100mA ; 1~400 MHz	ISO 11452-4
	EMC Compatibility - Magn.Field Imm.	15Hz ÷ 150 kHz	ISO 11452-8 : 2007
	Reverse Polarity Protection	-30V For 1h	ELEN PDV Rev. 3 - 5.3
	Overload Protection	24mA For 1h	ELEN PDV Rev. 3 - 5.6
	Overvoltage Protection	36V For 1h	ELEN PDV Rev. 3 - 5.7
	Output Short Circuit Protection	To Ground For 5' To VDC For 5'	ELEN PDV Rev. 3 - 5.4
	Supply Current (No Load)	30mA Max	ELEN PDV Rev.3 - 5.2
	Signal Output	[0.5V ÷ 5.5V]±0.2V	-
	Output Current	20mA Max	ELEN PDV Rev. 3 - 5.5
	Dielectric Rigidity	750V@50Hz For 60s	ELEN PDV Rev. 3 - 5.11
	ESD Protection	±8kV Contact , ±15 kV Air	EN 61000-4-2
	Insulation Resitance	1000 MOhm@500V	ELEN PDV Rev. 3 - 5.10
	Temperature Operating Voltage	30V@105°C For 1h	ELEN PDV Rev. 3 - 5.8
	Transient Voltage Protection	Pulses 1, 2A, 2B,3A, 3B, 4	ISO 7637-2 ; ISO 16750-2 (2012)
Environmental	Load Dump Transient	Test A (V supply 24V)	ISO 16750-2 (2012)
	Resolution	12 bit	-
	Linearity	< ±1%	-
	Operating Temperature (for Electronic Components)	-40°C ÷ +105°C	IEC 60068-2-1 ; IEC 60068-2-2 ; IEC 60068-2-30 ;IEC60068-2-14
Environmental	Storage Temperature (for the Assembly)	-25°C ÷ +105°C	IEC 60068-2-1 ; IEC 60068-2-2 ; IEC 60068-2-30 ;IEC60068-2-14
	Degree Of Protection	IP 67	IEC 60529
	Vibrations Resistance - Sine	(5÷12.87) Hz@dis±15mm ,(12,87÷200) Hz@dis<±15mm@5g, 1 Octave/min , 20 Sweep Cycles	IEC 60068-2-6 ISO15998
Mech.	Vibrations Resistance - Random	f=10Hz@PSD=1.44 g2/Hz ; f=100Hz@PSD=3.85 g2/Hz ; f=1000Hz@PSD=3.85 g2/Hz ; f=2000Hz@PSD=0.96 g2/Hz ; 3 Axis - 24h For Axis	IEC 60068-2-64 ENS0310 Rev.J
	Body Material	Aluminium With Antioxidant Treatment	-
	Ext.Shaft Material	Stainless Steel	-