







■ Angular Sensor




Ref.	Description	Operating temperature
1	Cable HT 105°C	-25 / +105
2	6 Pin Deutsch DT04-6P Connector	-55 / +125


 ELEN industrial vehicles sensors				www.elensrl.com		Elen Srl - Garbagnate Milanese (MI)		
				Date: 30/05/2017		Product Name: Angular Sensor $\pm 60^{\circ}$ 5V		
				Scale: 1 : 1		Double Output		
				Design: Mirko L.		Product Code: AA020560-13		
Review 1	Date 28/08/17	Signature Mirko L.	Last Review Description: Updated Output Sig.Charts and Tech.Spec.Table		Unit of Measurement: mm		Dimensions without tolerance indication: ISO 2768 - m	
						Page 1/2		

■ Output Signal


Signal 1 (V) @Vin = 5V




Signal 2 (V) @Vin = 5V



■ Functional Scheme



■ Typical Application



■ Technical Specifications

	Specific	Value	Standard Reference
Electrical	Power Supply (Vcc)	Min 4,5V - Max 5,5V	ELEN PDV Rev. 3 - 5.1
	EMC Compatibility	BCI - Class "A" - 100mA ; 1~400 MHz	ISO 11452-4
	Electrostatic Discharge Protection	±8kV Contact ; ±15kV Air Discharge	EN 61000-4-2
	Reverse Polarity Protection	-5.5V For 1h (-12V)	ELEN PDV Rev. 3 - 5.3
	Overload Protection	1.2 mA For 1h	ELEN PDV Rev. 3 - 5.6
	Overvoltage Protection	6.5V For 1h (20V)	ELEN PDV Rev. 3 - 5.7
	Output Current	Max 1 mA (For Channel)	ELEN PDV Rev. 3 - 5.5
	Maximum Load Recommended Output	>4.7 kOhm (For Channel)	-
	Supply Current (No Load)	15mA Max (For Channel)	ELEN PDV Rev. 3 - 5.2
	Linear Output (1)	0,5V ~ 4,5V (2.5V @0°)	-
	Linear Output (2)	0,5V ~ 4,5V (2.5V @0°)	-
	Resolution	< 0,1°	-
	Temperature Operating Voltage	5.5V @ 105°C For 1h	ELEN PDV Rev. 3 - 5.8
	Linearity	< ±1%	-
Environmental	Dielectric Rigidity	750V @ 50Hz For 60s	ELEN PDV Rev. 3 - 5.11
	Insulation Resistance	1000 MΩ @ 500V	ELEN PDV Rev. 3 - 5.10
	Shortcircuit Protection	To GND For 5' ; To Supply For 5'	ELEN PDV Rev. 3 - 5.4
	Operating Temperature	-40°C ~ +105°C	EN 60068-2-1;EN 60068-2-2; EN 60068-2-30;EN 60068-2-14
	Storage Temperature	-40° ~ +115°C	EN 60068-2-1;EN 60068-2-2; EN 60068-2-30;EN 60068-2-14
	Degree of Protection	IP 67	IEC 60529
	Vibrations Resistance - Sine	(5÷12.87)Hz@dis<±15mm, (12.87÷200)Hz@dis±15mm@5g, 1Octave/min, 20 Sweep Cycles	EN 60068-2-6 ISO 15998
	Vibrations Resistance - Random	f=10Hz@PSD=1.44 g2/Hz ; f=100Hz@PSD=3.85 g2/Hz ; f=1000Hz@PSD=3.85 g2/Hz ; f=2000Hz@PSD=0.96 g2/Hz ; 3 Axis - 24h For Axis	EN 60068-2-6
Mech.	Body Material	Aluminium With Antioxidant Treatment	-
	Shaft Material	Stainless Steel	-