







■ Angular Sensor



Details "B" (2 : 1)




Mating with 3-way Tyco
Superseal connector 282087-1


 ELEN industrial vehicles sensors			
Rev.	Date	Sign.	Review Description

www.elensrl.com		Elen Srl - Garbagnate Milanese (MI)	
Part Number:		AA301100-14	
Description:		Angular Sensor 10-30V ± 50°	
Designed	04/11/2022	Giulia M.	Scale : 1 : 1 (A3 format)
Checked			Dimensions without tolerance indication: ISO 2768 - m
Approved			 Units mm Page 1 / 2


■ Output Signal



■ Functional Scheme



■ Typical Application



■ Technical Specifications

	Specific	Value	Standard Reference
Electrical	Power Supply (Vcc)	10V Min ÷ 30V Max	PDV Rev. 3 - P. 5.1;
	Supply Current (No load)	20mA Max	PDV Rev. 3 - P. 5.2;
	Linear Output	See Picture Beside	-
	Output Current	20mA Max	PDV Rev. 3 - P. 5.5;
	Overload Protection	24mA For 1h	PDV Rev. 3 - P. 5.6;
	Overvoltage Protection	36V for 1h	PDV Rev. 3 - P. 5.7;
	Temperature Operating Voltage	30V @ 105° For 1h	PDV Rev. 3 - P. 5.8;
	Reverse Polarity Protection	-30V For 1h	PDV Rev. 3 - P. 5.3;
	Shortcircuit Protection	To Ground For 5' ; To Supply For 5'	PDV Rev. 3 - P. 5.4;
	Insulation Resistance	1000MΩ@500V	PDV Rev. 3 - P. 5.10;
	Dielectric Rigidity	750V@50Hz For 60s	PDV Rev. 3 - P. 5.11;
	ESD Protection	±8kV Contact; ±15kV Air	EN 61000-4-2;
	Transient Voltage Protection	Pulses 1, 2A, 2B , 3A , 3B , 4	ISO 7637-2; ISO 16750-2 (2012)
	Load Dump Transient	Test A (V supply 24V)	ISO 16750-2 (2012)
Environmental	Linearity	<±1%	-
	Resolution	<0.1°	-
	Operating Temperature (for Electronic Components)	-40°C ÷ +105°C	IEC 60068-2-14;IEC60068-2-1; IEC60068-2-2;IEC60068-2-30
	Storage Temperature (for the Assembly)	-40°C ÷ +105°C	IEC 60068-2-14;IEC60068-2-1; IEC60068-2-2;IEC60068-2-30
	Degree Of Protection	IP67	IEC 60529
	Vibrations Resistance - Random	f=10Hz@PSD=1.44g2/Hz; f=100Hz@PSD=3.85 g2/Hz, f=1000Hz@PSD=3.85g2/Hz, f=2000Hz@PSD=0.96g2/Hz; 3 Axes - 24h for Axis	IEC 60068-2-64; ENS 0310 Rev.J
	Vibrations Resistance - Sine	(5÷12.87)Hz@dis±15mm, (12.87÷200)Hz@dis<±15mm@5g, 1 Octave/min, 20 Sweep Cycles	EN 60068-2-6; ISO 15998
	EMC Compatibility - Magnetic Field Immunity	15Hz ÷ 150 kHz	ISO11452-8:2007;
	EMC Compatibility - BCI	BCI Class "A" - 100mA; (1÷400)MHz	ISO11452-4;
Mech.	Body Material	Nylon 6,6 + 30% G.F.	-
	Shaft Material	Stainless Steel	-