







■ Angular Sensor



Details "B" (2 : 1)




**Mating with 3-way Tyco
Superseal connector 282087-1**

 ELEN industrial vehicles sensors			
Rev.	Date	Sign.	Review Description


www.elensrl.com		Elen Srl - Garbagnate Milanese (MI)	
Part Number:		AA302001-5	
Description:		Angular Sensor 5V ±60°	
Designed	28/02/2024	Giulia M.	Scale : 1 : 0.75 (A3 format)
Checked	28/02/2024		Dimensions without tolerance indication: ISO 2768 - m
Approved	28/02/2024		Units mm
Page 1 / 2			

■ Output Signal


Signal (V) @Vin = 5V



■ Functional Scheme



■ Typical Application



■ Technical Specifications

	Specific	Value	Standard Reference
Electrical	Supply voltage (Vcc)	Min 4.5V - Max 5.5V	ELEN PDV Rev. 3 - 5.1
	Supply Current (No Load)	15 mA Max	-
	Output Signal	0.5V@-60° ÷ 4.5V@+60° (2.5V @0°)	-
	Output Current	1 mA Max	-
	Resolution	< 0.1°	-
	Linearity error	< 1%	-
	Reverse Polarity Protection	-5.5V For 1h (-20V For 1h)	ELEN PDV Rev. 3 - 5.3
	Overload Protection	1,2mA For 1h (20mA For 1h)	ELEN PDV Rev. 3 - 5.6
	Overvoltage Protection	6.5V For 1h (20V For 1h)	ELEN PDV Rev. 3 - 5.7
	Output Short Circuit Protection	To Ground For 5' To VDC For 5'	ELEN PDV Rev. 3 - 5.4
	Dielectric Rigidity	750V@50Hz For 60s	ELEN PDV Rev. 3 - 5.11
	Insulation Resitance	1000 MOhm@500V	ELEN PDV Rev. 3 - 5.10
	Temperature Operating Voltage	5.5V@105°C For 1h	ELEN PDV Rev. 3 - 5.8
	ESD Protection	±8kV Contact , ±15 kV Air	EN 61000-4-2
Environmental	EMC Compatibility	BCI - Class "A" - 100mA ; 1~400 MHz	ISO 11452-4
	EMC Compatibility - Magn.Field Imm.	15Hz ÷ 150 kHz	ISO 11452-8 : 2007
	Operating Temperature (for Electronic Components)	-40°C ÷ +105°C	IEC 60068-2-1 ; IEC 60068-2-2 ; IEC 60068-2-30 ; IEC60068-2-14
	Storage Temperature (for the Assembly)	-40°C ÷ +115°C	IEC 60068-2-1 ; IEC 60068-2-2 ; IEC 60068-2-30 ; IEC60068-2-14
	Degree Of Protection	IP 67	IEC 60529
Mech.	Vibrations Resistance - Sine	(5÷12.87) Hz@dis±15mm ,(12,87÷200) Hz@dis<±15mm@5g, 1 Octave/min , 20 Sweep Cycles	IEC 60068-2-6 ISO15998
	Vibrations Resistance - Random	f=10Hz@PSD=1.44 g2/Hz ; f=100Hz@PSD=3.85 g2/Hz ; f=1000Hz@PSD=3.85 g2/Hz ; f=2000Hz@PSD=0.96 g2/Hz ; 3 Axis - 24h For Axis	IEC 60068-2-64 ENS0310 Rev.J
	Body Material	Nylon 6.6 + 30% G.F.	-
	Shaft Material	Stainless Steel	-